secvest.®

FU5900

Secvest Key 2WAY Wireless Cylinder, O:30 / I:30 mm

The Secvest Key 2WAY wireless cylinder is an optional accessory for the Secvest 2WAY. It is the first cylinder lock which automatically deactivates the alarm system when it is unlocked and activates it when it is locked. An LED on the Secvest Key 2WAY always indicates the current status of the alarm system.
Installing the wireless cylinder is extremely easy: Pull the old cylinder out and insert the wireless cylinder. The door knob is located at the inside of the door. Attach the Secvest 2WAY Key with a forend screw – ready. The wireless cylinder fits all doors with Euro profile. It can be integrated in all ABUS locking systems and is also available for cylinder systems from other manufacturers.
After the wireless cylinder is taught–in to the system, the usual "unlocking the door" suffices to disarm the alarm system. To arm the system, the button on the rotating door knob must be pressed before the door is closed. You can lock the door without pressing this button, but the system will not be armed.

Product highlights:

- First wireless arming cylinder in the world
- Convenient arming and disarming the Secvest 2WAY
- One–button operation
- Acoustic status notification
-

The wireless cylinder comes in different sizes of the outer dimension (O) and inner dimension (I) from 30 / 30 mm to 70 / 75 mm. You can find the correct cylinder length as follows:

Determine the outer dimension by measuring the distance from the center of the fastening bolt to the outside of the plate (or of the strike plate).

Determine the inner dimension by measuring the distance from the center of the fastening bolt to the inside of the plate (or of the strike plate). Round up to the next larger 5 mm interval. Example: If you measure an inner dimension of 33 mm, you need a cylinder of 35 mm inner length.

3 keys are included in the scope of delivery. You can order a suitable replacement key for the Secvest 2WAY wireless cylinder at any time or have a copy made at a lock and key service.

© 2012 ABUS Security–Center GmbH & Co. KG, Errors and omissions excepted.

secvest.®

FU5900

Secvest Key 2WAY Wireless Cylinder, O:30 / I:30 mm

Technical Data	
power supply	3V lithium
Type of battery	CR2477N
Battery service life	approx. 12 months
Temperature range	–10 to +55 °C
Environmental class	2
Wireless radio	868MHz, narrow band "security band"
Output	10mW
Inner dimensions	30mm
Outer dimensions	30mm

© 2012 ABUS Security–Center GmbH & Co. KG, Errors and omissions excepted.